

# O-LEG Spec Sheet

## Specifications

Welded for maximum strength and stability

Tubing: 1 x 2-1/2" Steel

Mounting Plate:

- Fabricated steel
- Requires (16) #12-14 screws (not supplied)

Finish: Powder coat finish as standard, 12 available colors

Stretchers available



Part #	Column Size	Recommended Max. Top Depth	Base Spread	Weight	Height
2250	1" x 2-1/2"	18"	17-1/2"	14 lbs.	27-3/4"
2251	1" x 2-1/2"	24"	23-1/2"	16 lbs.	27-3/4"
2252	1" x 2-1/2"	30"	29-1/2"	18 lbs.	27-3/4"
2253	1" x 2-1/2"	36"	35-1/2"	20 lbs.	27-3/4"

Part #	Column Size	Recommended Max. Top Depth	Base Spread	Weight	Height
CH2250	1" x 2-1/2"	18"	17-1/2"	16 lbs.	34-3/4"
CH2251	1" x 2-1/2"	24"	23-1/2"	18 lbs.	34-3/4"
CH2252	1" x 2-1/2"	30"	29-1/2"	20 lbs.	34-3/4"
CH2253	1" x 2-1/2"	36"	35-1/2"	22 lbs.	34-3/4"

Part #	Column Size	Recommended Max. Top Depth	Base Spread	Weight	Height
B2250	1" x 2-1/2"	18"	17-1/2"	19 lbs.	40-3/4"
B2251	1" x 2-1/2"	24"	23-1/2"	21 lbs.	40-3/4"
B2252	1" x 2-1/2"	30"	29-1/2"	23 lbs.	40-3/4"
B2253	1" x 2-1/2"	36"	35-1/2"	25 lbs.	40-3/4"

**Stretchers are recommended on counter height and bar height bases.  
When ordering bases with stretchers add prefix "S" to part # (ex BS2252)**

## Options

- **Unfinished/Raw**
- **Special Heights:**
  - Shorter heights available
- **Castors:**
  - Hard Wheel: Add prefix "C" to part #
  - Soft Wheel: Add prefix "D" to part #