

# PROPEL Y BASE

## Spec Sheet

An optional stretcher bar is available for larger tops. The stretcher bar should be used with tops that are larger than 30" wide x 60" long. Tops that are 30" wide x 60" long or less do not require a stretcher bar.

Part #	Column Size	Recommended Max. Top Depth	Base Spread	Weight	Stretcher
5632	2-1/4" Dia.	24"	17-1/2"	10 lbs.	Optional
5634	2-1/4" Dia.	30"	22-3/4"	11 lbs.	Optional
S5635	2-1/4" Dia.	36"	29"	12 lbs.	Required
S5636	2-1/4" Dia.	48"	33-3/8"	18 lbs.	Required

### Specifications

Base is a bolted, welded combination

Column 2-1/4" OD x 13ga, Feet Cast Aluminum

Mounting Plate:

- Parts 5632 and 5634 use 6" x 8" steel plate and requires (6-8) #12-14 screws (not supplied)
- Part S5635 uses 8" x 8" steel plate
- Part S5636 uses 12" x 12" steel plate
- Requires (12) #12-14 screws (not supplied)

Base Height: 27-3/4"

Finish: Powder coat finish as standard, 12 available colors

Patented Base



### Options

- **Unfinished/Raw**
- **Polished or Satin Chrome**
- **Special Heights:**
  - Shorter and taller heights available
  - Bar Height, add prefix "B" to part #
- **Casters:**
  - Hard Wheel: Add prefix "C" to part #
  - Soft Wheel: Add prefix "D" to part #
- **Modify to accept Stretcher:**
  - Add prefix "S" to part #
- **Self-Leveling Glides:**
  - Add prefix "K" to part #
  - Self-Leveling glides do add approx. 3/4" to base height
- **Adjustable Spring Clip:**
  - Height range 24-3/4" - 33-3/4": add prefix "AH" to part #
  - Height range 27-3/4" - 40-3/4": add prefix "AHB" to part #
- **Flip-Top w/ Handle Release:**
  - Add prefix "H" to the part #
  - Only available on parts 5632, 5634, and S5635
- **Wire Holes:**
  - Add prefix "W" to part #
  - Includes (2) 1-1/4" removable grommets
  - Holes are 1-1/2" x 2-1/4" with grommets removed