ROUND H LEG

Spec Sheet

Part #	Column Size	Recommended Max. Top Depth	Base Spread Center to Center on column	Weight
2208	2" Dia.	8" Base Spread. Application is extra support	8"	13 lbs.
2200	2" Dia.	18"-22"	11"	15 lbs.
2214	2" Dia.	19"-24"	14.25"	15 lbs.
2220	2" Dia.	27"-36"	20"	18 lbs.
3314	3" Dia.	19"-24"	14.25"	17 lbs.
3320	3" Dia.	27"-36"	20"	19 lbs.
3324	3" Dia.	37"-48"	24"	21 lbs.
4424	4" Dia.	42"-48"	24"	30 lbs.
4430	4" Dia.	49"-60"	30"	34 lbs.

Specifications

Welded for maximum strength and stability

Tubing:

- 2" Column, 14 gage wall
- 3" and 4" Column, 16 gage wall

Mounting Plate:

- Part 2208, fabricated steel 6" x 11-1/2"
- Part 2214, fabricated steel 6" x 18"
- Parts 2220 and 3320, fabricated steel 6" x 26"
- Parts 2200 and 3324, fabricated steel (2) 6" x 6"
- Parts 4424 and 4430, steel plates (2) 8" x 8"
- Requires (8) #12-14 screws (not supplied)

Base Height: 27-3/4"

Finish: Powder coat finish as standard, 12 available colors



Options

- Unfinished/Raw
- Special Heights:
 - Shorter and taller heights available
 - O Bar Height, add prefix "B" to part #
- Casters:
 - O Hard Wheel: Add prefix "C" to part #
 - Soft Wheel: Add prefix "D" to part #
 - Only available on 2" Legs
- Adjustable Spring Clip (only available on 2"):
 - O Adjusts in 1" increments
 - Height range 24-3/4" 33-3/4": add prefix "AH" to part #
 - Height range 27-3/4" 40-3/4": add prefix "AHB" to part #

