

ROVE X BASE

Spec Sheet

Part #	Column Size	Recommended Max. Top Depth	Base Spread	Weight
2829	3" Dia.	24" Round	22" x 22"	24 lbs
2830	3" Dia.	36" Round	26" x 26"	25 lbs
2831	3" Dia.	42" Round	32" x 32"	28 lbs
2832	3" Dia.	60" Round	38" x 38"	32 lbs

Specifications

Rigid Bolted and welded combination

Assembly of column to "X" required.

Column 3" OD x 16ga, Foot is fabricated steel

Mounting Plate:

- Fabricated steel 8" x 8" and 12" x 12"
- Requires (12) #12-14 screws (not supplied)

Base Height: 27-3/4"

Finish: Powder coat finish as standard, 12 available colors

Patented Base



Options

- **Unfinished/Raw**
- **Polished or Satin Chrome**
- **Special Heights:**
 - Shorter and taller heights available
 - Bar Height, add prefix "B" to part #
- **Casters (3"):**
 - Soft Wheel: Add prefix "C" to part #
- **Self-Leveling Glides:**
 - Add prefix "K" to part #
 - Self-Leveling glides do add approx. 3/4" to base height
- **Flip-Top:**
 - Add prefix "FT"
 - Maximum top size is 48" with casters
- **Power Box Wire Management:**
 - A steel box mounting plate with a 9.6" x 9.6" x 2.75" tall I.D. allows room for a power module to be concealed. Wire and plug travel down the inside of the column and out a hole near the bottom of the column. Box is powder coated to match base.
 - Hole in column is 1.5" diameter.
 - Add prefix "W" and suffix "-0005" to part #
 - Example: W2831-0005